

Pana 21:9 Displays

Pana 105 Interactive
Pana 105 Display

Pana 81 Interactive
Pana 81 Display



Pana 21:9 Displays

- **21:9 in native 5K resolution**
- **Interactive and Display versions**
- **Preloaded with SimpleShare®**

See the World through a 21:9 Lens

Pana's 21:9 ultra-wide 5K resolution brings a refreshing form factor to the conventional display market. Our 8-foot wide Pana 105 canvas optimizes team productivity allowing for improved interaction and work place collaboration.

The market most receptive to this format are enterprise and industrial companies leaning into visualization technology to be their focal point and center piece. CIOs are telling us 21:9 is making the biggest impressions enabling them to stand out, land new clients and attract better talent. That's a win-win.

Lightweight and maneuverable, the Pana is ideal for retrofits as all sizes fit into a commercial service elevator and can be mounted using standard industry hardware without reinforced concrete or steel backing. Pana's lower infrastructure costs equates to a lower cost of ownership as a result of easy retrofit, reduced energy consumption and affordable price point. All Pana displays are Energy Star certified.

PANA FEATURES

21:9 Panoramic

The extra wide form factor is inspired by our natural human ability to see wider than we see taller.

5K Resolution

Pana provides 33% more pixels with 5K resolution giving the user more real estate in which to work.

Interactive User Experience

Touch enables the expectation for interactive autonomy, speed and ease-of-use. Pana interactive displays are touch driven by multiple, simultaneous collaborators.

Built for Human Interaction

More pertinent information gets placed in our visual sweet spot increasing our comprehension and productivity. And all the pixels are placed where everyone on the team can reach them preserving our dignity among our peers of not having to overreach or bend over to interact with the display.

Interactivity through SimpleShare®

Jupiter's proprietary SimpleShare software enables intuitive interaction optimized for Pana displays. The platform provides quick and easy access to your daily workflow.

Pana 21:9 Displays Specifications

	Pana 105 Interactive	Pana 105 Display	Pana 81 Interactive	Pana 81 Display
SPECIFICATIONS				
Model Name	Pana 105T	Pana 105D	Pana 81T	Pana 81D
Resolution	5120 x 2160	5120 x 2160	5120 x 2160	5120 x 2160
Orientation	Landscape	Landscape or Portrait	Landscape or Portrait	Landscape or Portrait
Screen Size	105" (2667mm) diagonal	105" (2667mm) diagonal	81" (2057mm) diagonal	81" (2057mm) diagonal
Contrast Ratio	1800:1	1800:1	1800:1	1800:1
Brightness	450 cd/m ²	600 cd/m ²	450 cd/m ²	600 cd/m ²
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Viewing Angle	178° H/V	178° H/V	178° H/V	178° H/V
Lifetime	≥ 50,000 Hrs	≥ 50,000 Hrs	≥ 50,000 Hrs	≥ 50,000 Hrs
Response Time	8 ms	8 ms	8 ms	8 ms
Display	21:9 aspect ratio, anti-glare, IPS LCD with local dimming, direct-bonding IR with 20 simultaneous touch points	21:9 aspect ratio, anti-glare, IPS LCD with local dimming	21:9 aspect ratio, anti-glare, IPS LCD with local dimming, bezel-less metal-mesh capacitive with 20 simultaneous touch points	21:9 aspect ratio, anti-glare, IPS LCD with local dimming
HDCP Support	2.2	2.2	2.2	2.2
POWER				
Input Current	6A	6A	6A	6A
Power Standby	≥ 0.5 W	≥ 0.5 W	≥ 0.5 W	≥ 0.5 W
Internal Speaker Output	2 x 15 W	2 x 15 W	2 x 15 W	2 x 15 W
Avg Power Consumption	140 W	140 W	140 W	140 W
Max Power Consumption	600 W	600 W	500 W	500 W
USB-C PD Output	65W	65W	65W	65W
Operating Temperature	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)
CONNECTIVITY				
DisplayPort 1.4 In	1	1	1	1
DisplayPort 1.4 Out	1 (MST)	1 (MST)	1 (MST)	1 (MST)
HDMI 2.0 In	2	1	2	1
OPS Slot	1	1	1	1
USB-C	1	1	1	1
USB 2.0 Type-A	4	4	4	4
3.5mm Line Out	1	1	1	1
S/PDIF Optical Fiber	1	1	1	1
100M Ethernet	1	1	1	1
RS232	1	1	1	1
ACCESSORIES				
Ships With	Pana user manual, power cable, remote control & batteries	Pana user manual, power cable, remote control & batteries	Pana user manual, power cable, remote control & batteries	Pana user manual, power cable, remote control & batteries
Pana OPS (Optional)	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.
Pana Pen (Optional)	Active Pcap Smart Pen, Pen & Windows Ink support.	Active Pcap Smart Pen, Pen & Windows Ink support.	Active Pcap Smart Pen, Pen & Windows Ink support.	Active Pcap Smart Pen, Pen & Windows Ink support.
DIMENSIONS				
Dimensions	99.2" x 43.5" x 4.3" (2520mm x 1105mm x 109mm)	96.5" x 40.7" x 3.7" (2450mm x 1034mm x 94mm)	76.1" x 33.3" x 3.4" (1933mm x 847mm x 86mm)	75.6" x 32.7" x 3.3" (1919mm x 830mm x 83mm)
Weight	207 lbs (94 kg)	135.5 lbs (61.5 kg)	117 lbs (53 kg)	77 lbs (35 kg)
Shipping Dimensions	109.4" x 59" x 13" (2780mm x 1500mm x 330mm)	105.5" x 55.1" x 12.6" (2680mm x 1400mm x 320mm)	84.4" x 40.0" x 10.3" (2145mm x 1015mm x 262mm)	84.4" x 40.0" x 10.3" (2145mm x 1015mm x 262mm)
Shipping Weight	258 lbs (117 kg)	192 lbs (87 kg)	141 lbs (64 kg)	105 lbs (47 kg)
VESA Mount Dimensions	1500mm x 500mm	1500mm x 500mm	800mm x 400mm	800mm x 400mm
Mount Dimensions	1500mm x 600mm	1500mm x 600mm	800mm x 400mm	800mm x 400mm
CERTIFICATIONS				
Regulatory Certifications	UL, CB, CE, FCC, CA65, Energy Star, RoHS Compliant	UL, CB, CE, FCC, CA65, Energy Star, HDR400, RoHS Compliant	UL, CB, CE, FCC, CA65, Energy Star, HDR400, RoHS Compliant	UL, CB, CE, FCC, CA65, Energy Star, HDR400, RoHS Compliant

Pana 105 shown in Portrait and Landscape orientations.



jupiter.com

© 2021 Jupiter. Jupiter is a registered trademark of Jupiter Systems, Inc. Product specifications and designs are subject to change without notice. All brand and product names and logos are registered trademarks of Jupiter Systems, Inc.

DS_PANA_MARCH2022