



Umake OF Series

Umake OF2 Sphere Screen

Product Features:

- 3840Hz High Refresh Rate, No Screen Flicker
- 240W/m² Low Power Consumption, Cost Saving
- Seamless Design, Smooth Display Screen
- Magnetic Design, Efficient Installation

SPECIFICATION PARAMETERS:

Specification	Umake OF2							
Diameter (m)	1	1.2	1.5	2	2.5	3	3.5	4
Area (m ²)	3.14	4.52	7.07	12.56	19.63	28.26	38.47	50.24
Pixel Pitch	2 mm							
LED Type	SMD							
Resolution (Overall)	1571	1885	2356	3142	3927	4712	5498	6283
	x786	x943	x1178	x1571	x1964	x2356	x2749	x3142
Module Seam	≤0.25 mm							
Module Installation Method	Magnet							
Weight	78kg	113 kg	175 kg	352 kg	552 kg	795 kg	1100 kg	1750 kg
Contrast Ratio	4500:1							
Brightness	≥600 nits							
Refresh Rate	3840 Hz							

Gray Scale	14 bit
Color Temperature	5500-9500 K (Adjustable)
Peak Power Consumption	720 W/m ²
Typical Power Consumption	240 W/m ²
Viewing Angle	(H)160°/(V)140°
Input Voltage	AC100V~240V
Operating Voltage	DC4.2V~4.6V
Ingress Protection	IP31
Installation Method	Front
Maintenance Method	Lifting/fixing
Operating Temperature/ Humidity	-10°C~+45°C/ 10~80%RH (No Freeze)
Storage Temperature/ Humidity	-20°C~+55°C/ 10~85%RH (No Freeze)

Note:

1. Product pictures are for illustration only, the actual product effects (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product;
2. The specification parameters are reference values. Part of the data comes from Unilumin's internal laboratory and is obtained under a specific test environment. In actual use, it may be slightly different due to product batch differences, configuration differences, software versions, use conditions and environmental factors. Actual usage shall prevail.